

HANSEN®

THE WIZARD

GENERAL

- Time Coherent
- Dispersion Coherent
- Frequency Response: 29 hz to 23,000hz +/-2db
- Sensitivity: 87db
- Nominal Impedance: 6 Ohms
- True Dynamic
- Tonal Accurate

TWEETER

- Engineered, designed and manufactured for Hansen Audio
- 25mm high performance dome mounted on a dispersion optimized 6mm aluminum plate
- Precision assembled

WOOFERS

- Engineered, designed and manufactured by Hansen Audio
- 182 mm driver x 2
- Exotic multi-layer composite sandwich cone
- Optimized geometry "Hansen motor system"
- Hand assembled "Hansen Architecture" frames
- *Sound Wave Deformation Prevention*

ENCLOSURE

- Engineered, designed, and manufactured by Hansen Audio
- "Hansen Composite Matrix" material hybrid design with Class "A" finish
- Hansen Audio "CLOAKING DEVICE"
- *Sound Wave Diffraction Distortion Elimination* technology
- Acoustically inert

CROSSOVER

- Engineered, designed and manufactured by Hansen Audio
- V2 DAT (*Driver Assimilation Technology*)
- Frequency and phase optimized
- Hand assembled
- High grade hand selected components
- Point to point silver solder connections

TERMINAL CONNECTIONS

- High current pole terminal
- Decreased transition resistance



WEIGHT - 140 lbs. (with crate)

SIZE

- Height: 17 inches
- Width: 24 inches
- Depth: 19 inches

FINISHES

- Hansen Audio Silver
- Hansen Audio Black

GRILLS

- Driver protection grills included
(to be removed during critical listening)

Head Office:

HANSEN AUDIO Inc.

100 Leek Cres., Unit 9
Richmond Hill, Ontario
L4B 3E6

Phone: 905 731.8434

Fax: 905 737.8420

WWW.HANSENAUDIO.COM